

(19) 世界知识产权组织
国际局(43) 国际公布日:
2005年6月16日(16.06.2005)

PCT

(10) 国际公布号:
WO 2005/055510 A1

- (51) 国际分类号⁷: H04L 7/00, H04J 3/00
- (21) 国际申请号: PCT/CN2004/001379
- (22) 国际申请日: 2004年11月30日(30.11.2004)
- (25) 申请语言: 中文
- (26) 公布语言: 中文
- (30) 优先权:
200320127259.X 2003年12月5日(05.12.2003) CN

(71) 申请人(对除美国以外的所有指定国): 华为技术有限公司(HUAWEI TECHNOLOGIES CO., LTD.) [CN/CN]; 中国广东省深圳市龙岗区坂田华为总部办公楼, Guangdong 518129 (CN).

(72) 发明人;及

(75) 发明人/申请人(仅对美国): 蒋章展(JIANG, Zhangzhen) [CN/CN]; 彭忠文(PENG, Zhongwen) [CN/CN]; 唐勇(TANG, Yong) [CN/CN]; 权星月(QUAN, Xingyue) [CN/CN]; 中国广东省深圳市龙岗区坂田华为总部办公楼, Guangdong 518129 (CN).

(74) 代理人: 北京集佳知识产权代理有限公司(UNITALEN ATTORNEYS AT LAW); 中国北京市朝阳区建国门外大街22号赛特广场7层 Beijing 100004 (CN).

(81) 指定国(除另有指明, 要求每一种可提供的国家保护): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW


(84) 指定国(除另有指明, 要求每一种可提供的地区保护): ARIPO(BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), 欧亚专利(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), 欧洲专利(AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

本国际公布:
— 包括国际检索报告。

所引用双字母代码和其它缩写符号, 请参考刊登在每期PCT公报期刊起始的“代码及缩写符号简要说明”。

(54) Title: TRIBUTARY UNIT OF SYNCHRONOUS DIGITAL HIERARCHY AND SDH APPARATUS NODE

(54) 发明名称: 同步数字传送体系支路单元以及SDH设备节点



(57) Abstract: A tributary unit of Synchronous Digital Hierarchy supporting multiple services processing, wherein comprises a SDH tributary process module and at least two service process modules, and the SDH tributary process module is connected with each of the service process modules, which performs mapping and demapping to the service signal respectively. Each of the service process modules can be connected with the local interface directly, and there is a multiple services cross process module in tributary unit, which is connected with said service process modules respectively and achieves the interworking between the different services. The present utility model can decrease the number of single boards, avoiding the usage of external meshwire or apparatus, and can save costs of apparatus, be convenient to maintain and increase the apparatus reliability.

[见续页]